



## Specifications ...

(Indicative Picture)

### ALTERNATOR

Frequency	Hz	50
Output Rating	Continuous	125
(kVA)	Standby	138
No. of Phases		Three-Phase, 4 Wire
Rated Voltage	V	Line to Line 50Hz: 190-215(220) or 380-430
Power Factor		0.8
Voltage Regulation	%	Within + 0.5
Excitation		Brushless, Rotating Exciter (with A.V.R.)
Insulation		Class F

### ENGINE

Make & Model		Komatsu S6D108E-2-A
Type		Inlined, Direct Injected Turbo
Output Rating		
	PS/rpm	153 / 1500
	KW/min-1	113 / 1500
No. of Cylinders-Bore X Stroke	mm	6 - 108 x 130
Piston Displacement	L	7.15
Fuel		Diesel
Fuel Consumption	L/H	18.9
Lube Oil Sump Cap	L	31
Coolant Capacity	L	29.4
Battery Capacity	V-Ah	95E41RX2
Fuel Tank Capacity	L	250

### UNIT

Dimensions (mm)	Length	3350
	Width	1200
	Height	1500
Dry Weight	Kg	2740

### SOUND LEVEL

7m/dB (A) 1500rpm	(min-1)	65
-------------------	---------	----