



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE POWER

POWERED by
HONDATM



Technical

Model	GH 10,000E-LRT
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	9.0 kW
Continuous Output	11.0 kVA
Noise Level (dBA @ 7m)	74
Frame	Extra Large roll frame

Engine

Manufacturer	Honda
Engine Model	GX610
Type	O.H.V.
Starting	Electric start
Fuel	Unleaded Petrol
Run Time	4.2hrs @60%
Tank Capacity	15 L
HP 3000 rpm cont	11.9 HP
Cubic Capacity	614 Cm ³
Oil Capacity	1.8 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	2 x 15amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	86 Cm
Width	50 Cm
Height	57 Cm
Weight	140 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Wheel kits	Four wheel
Frames	Fuel Tank Base with Roll Over Frame
Alternators	Oversized, Single or Three Phase