



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE POWER

Technical

Model	GH 10,000E-LRT
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	9.0 kW
Continuous Output	11.0 kVA
Noise Level (dBA @ 7m)	74
Frame	Extra Large roll frame

Engine

Manufacturer	Honda
Engine Model	GX610
Type	O.H.V.
Starting	Electric start
Fuel	Unleaded Petrol
Run Time	4.2hrs @60%
Tank Capacity	15 L
HP 3000 rpm cont	11.9 HP
Cubic Capacity	614 Cm ³
Oil Capacity	1.8 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	2 x 15amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	86 Cm
Width	50 Cm
Height	57 Cm
Weight	140 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Wheel kits	Four wheel
Frames	Fuel Tank Base with Roll Over Frame
Alternators	Oversized, Single or Three Phase

POWERED by
HONDA™

meccalte spa

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.