



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE POWER

Technical

Model	GH 2000
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	2.2kW
Continuous Output	2.5kVA
Noise Level (dBA @ 7m)	72
Frame	Small roll frame

Engine

Manufacturer	Honda
Engine Model	GX160
Type	O.H.V.
Starting	Recoil start
Fuel	Unleaded Petrol
Run Time	3.1hr @ 100%, 5hrs @ 60% Load
Consumption	1.2 L/h
Tank Capacity	3.6 L
HP 3000 rpm Continuous	3.4
Cubic Capacity	163 Cm ³
Oil Capacity	0.6 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	2 x 10amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	67 Cm
Width	44 Cm
Height	48 Cm
Weight	33 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long Range Tank	15 Litre Capacity

POWERED by
HONDA™

meccalte spa

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.