



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE POWER

POWERED by
HONDA™



Technical

Model	GH 6000
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	6.0kW
Continuous Output	7.5kVA
Noise Level (dBA @ 7m)	72
Frame	Extra Large roll frame

Engine

Manufacturer	Honda
Engine Model	GX390
Type	O.H.V.
Starting	Recoil start
Fuel	Unleaded Petrol
Run Time	2.6 hr @ 100%, 3.8hrs @60%
Tank Capacity	6.1 L
HP 3000 rpm cont	8.0 HP
Cubic Capacity	389 Cm ³
Oil Capacity	1.1 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	10amp + 15amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	76 Cm
Width	50 Cm
Height	57 Cm
Weight	75 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Wheel kits	Two wheel or four wheel
Frames	Extra large Roll Frames
Alternators	Oversized, Single or Three Phase
Long Range Tank	15 Litre Capacity