


4 in 1 Work Station



CIVILPRO
GENERATOR & WELDER
RENTALS & HIRE

0411 961 231 WWW.CIVILPRO.COM.AU

GHWS200E



PORTABLE POWER



POWERED by
HONDA™

Technical Data

Model	GHWS200E
Type	Portable
Speed	3000 RPM
Frequency	50 Hz
Max Power W	5600
Duty cycle 35 %	200 A
Duty cycle 60%	180 A
Voltage	240
Stricking volts	75 V
Noise Level (dBA @ 7 m)	76
Compressor	196LPM 2HP
Compressor Tank Capacity	25 Litres
Battery Charger	12vdc 10amp

Engine

Brand	Honda
Type Engine	GX 390
Distribution	O.H.V.
Starting	Reoil start / Electric start
Fuel	Unleaded petrol
Duration	2.7 h
Consumption	2.4 L/h
Tank	6.5 L
Protection	low oil level
HP 3600 rpm max	13
Cubic Capacity	389 Cm ³
Oil Capacity	1.1 L

Alternator

alternator type	Sincro
regulator	Brushless
protection class	IP 23
insulation class	Class H

Accessories

Leads	Five Metre welding leads
Outlets	10amp & 15amp Switched With Thermal Overload

Dimensions and Weight

Length	96 Cm
Width	70 Cm
Height	70 Cm
Weight	120 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long range Tank	15 Litre Capacity
Wheel kits	Two wheel or four wheel
Battery	Dry Charged

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only