



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



DEPENDABLE POWER

400 Series Perkins Diesel



Stamford Alternator



Deep Sea Controls



Technical

Model	OZP20SA
Type	Heavy Duty
Speed	1500 RPM
Phase/Voltage	3, 240/415
Frequency	50 Hz
Stdby Power kVA/kW	22kVA / 17.6kW
Prime Output kVA / kW	22kVA / 16kW
Noise Level (dBA @ 7m)	60dB(A)
Fuel Capacity	24 Hrs 130 Litres

Engine

Manufacturer	Perkins Diesel
Engine Model	404D-22G
Type & Cylinder	4 Stoke - 4 L
Induction	Naturally Aspirated
Fuel Consumption	5.4 L @ 100%, 4.0L @ 75%, 2.9L @ 50% Load
Coolant Capacity	7 L
Governor	Mechanical
Cubic Capacity	2.2 L
Oil Capacity	10.6 L

Alternator

Alternator Brand / Model	Stamford / PI144H
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Canopy

Skid	Bunded fuel tank with fork lift pockets and skid tie down points
Canopy	Centre Lift, lockable doors with control panel viewing window
Paint Finish	Heavy duty powder coat finish white canopy with a black base
Emergency Stop	External Emergency Stop Fitted

Dimensions & Weight

Length	1.81m
Width	1.05m
Height	1.32m
Weight	840 Kg

Controls

Controller	Deep Sea 702 with Analogue Metering
Circuit Breaker	Four Pole RCD MCBO
Battery Isolator	Fitted within canopy adjacent battery

Outlets

Outlets 3 Phase	1 x 32amp 5pin IP66 c/w RCD & C/B
Outlets 1 Phase	3 x 15amp 3pin IP66 c/w RCD & C/B
PMG Option	Available with PI144H